

# Mosaic

## Beech in strips

MOSAIC RANGE



**DESIGN PARQUET**

654 rue du Chalonge, P.A. du Haut-Montigné / 35370 Torcé / FRANCE  
Tél. +33 (0)2 99 49 66 66 / Fax +33 (0)2 99 49 66 67  
E-mail France : [commercial@designparquet.fr](mailto:commercial@designparquet.fr)  
E-mail Export : [export@designparquet.fr](mailto:export@designparquet.fr)

[www.designparquet.com](http://www.designparquet.com)

Previous data sheet are invalid. Errors or technical informations can  
be changes without notice.  
Updated in : January 2026.

# DATA SHEET - MOSAIC

## CHARACTERISTICS

**Species (origin) :** Beech (Europe).

*Other species on request.*

**Description :** Light brown wood, ranging from cream white to pale pink, sometimes with reddish areas towards the center. Characteristic fine grain. Sometimes wavy fiber.


**Grade :** PR (PRIME) : Small knots up to 10 mm, sapwoodless, slight colour variations.

**Support :** Solid.

**Density :** 710 kg/m<sup>3</sup>.

**Type :** Mosaic (Beech in strips).

**Finishing :** Unfinished (filling necessary during the process of installation).



SUPPORT	THICKNESS (MM)	SIZE (MM)	TYPE	BEVELS	THERMAL RESISTANCE K/W
SOLID	8	480 x 480*	Mosaic	NO	0,04 m <sup>2</sup>

\* assembly (strips of 120 x 24 mm) with a thermoplastic net.

## TYPE OF INSTALLATION

- Glued according to NF DTU 51-2.

The mosaics must be glued on their side covered with a thermoplastic net.

## COMPATIBILITIES

Not compatible on low temperature hydraulic underfloor heating and cooling.

## MAINTENANCE FLOOR


After finish :

- Remember to put protective pads under the legs of chairs and furniture.
- Carry out regular maintenance with a vacuum cleaner, broom, woollen cloth.
- Never wash your floor with large amounts of water.
- Do not use aggressive, abrasive, silicone or ammonia detergents.
- For persistent stains, remove with a damp sponge and neutral detergent.

## INFORMATIONS

- Air humidity at the time of laying and throughout the life of the product must be between 40% and 60%.
- Fire classification :
  - Cfl-s1 (Solid)
- Hardness rank : C.
- Beech Monnin hardness : 4,2.

## VOC EMISSIONS



\*Information on the level of volatile compounds emission in inside air, that present a toxicity risk by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

## RANKING USE

The classification of parquet flooring is based on the class of use. The UPEC\* classification does not apply to parquet flooring insofar as it can be renovated, but an equivalence can be made :

SUPPORT	THICKNESS (MM)	RANK	UPEC EQUIVALENCE
SOLID	8		U3S P3 E1 C0

\* Wear, punching, water, chemistry.