

# Urban

PRIMO NATURAL RANGE

## CHARACTERISTICS

**Species (origin) :** Oak (Europe).

**Grade :** PRIME BIS (PR-BIS) : Small knots up to 15 mm, without sapwood, slight colour variations (possible discoloration).

**Support :** Solid.

**Density :** 650 kg/m<sup>3</sup>.

**Finishing :** Matt varnish.

**Assembly :** Tongue and groove (T+G).

SUPPORT	SIZE (MM)	LENGTHS (MM)	BEVELS	THERMAL RESISTANCE K/W
SOLID	14 x 130	400-1200	4	0,09 m <sup>2</sup>

## TYPES OF INSTALLATION

- Glued (according to NF DTU 51-2).

## COMPATIBILITIES

Compatible on low temperature hydraulic underfloor heating and cooling (according size) :

COMPATIBILITIES			GLUED LAYING	
SUPPORT	THICKNESS (MM)	WIDTH (MM)	HEATING UNDERFLOOR	HEATING/COOLING UNDERFLOOR
SOLID	14	130	YES	YES

It is imperative to start the heating 4 weeks before the beginning of the laying. Heater off 48 hours before laying. Wait for 1 week and restart the heating gradually over 15-20 days. It is traditionally recommended a thermal resistance less than or equal to 0.09 m<sup>2</sup>.K/W. For higher thermal resistances, a certain loss of capacity must therefore be considered.

It is imperative to respect the laying rules and the manufacturer's recommendations for use, as well as the governing regulations :

- NF DTU 35.14 – Execution of hot water floors.
- The CSTB 3164 booklet – Reversible floors.

Suitable with ISO dB and Iso alu (Cf data sheet).

## INFORMATIONS


- Air humidity at the time of laying and throughout the life of the product must be between 40% and 60%.
- Fire classification :
  - Cf1-s1 (according to EN NF 14342)
- Hardness rank : C.
- Oak Monnin hardness : 4,2.

## FLOOR MAINTENANCE

After laying, apply two coats of  **Renovator matt** on new parquet (metallising), and repeat the operation once or twice a year or more if necessary. It is applied undiluted with a microfiber mop (follow the instructions for use). For difficult stains or to remove old coats of Metalliser, consider the Overactivated Cleaner. Routine maintenance should be carried out with  **cleaner**.

- Remember to put protective pads under the legs of chairs and furniture.
- Carry out regular maintenance with a vacuum cleaner, broom, woollen cloth.
- Never wash your floor with large amounts of water.
- Do not use aggressive, abrasive, silicone or ammonia detergents.
- For persistent stains, remove with a damp sponge and neutral detergent.

## VOC EMISSIONS



\*Information on the level of volatile compounds emission in inside air, that present a toxicity risk by inhalation, on a scale from A+ (very low emissions) to C (high emissions).

## RANKING USE

The classification of parquet flooring is based on the class of use. The UPEC\* classification does not apply to parquet flooring insofar as it can be renovated, but an equivalence can be made :

SUPPORT	THICKNESS (MM)	RANK	UPEC EQUIVALENCE
SOLID	14		U3s P3 E1 Co

\* Wear, punching, water, chemistry.

## DESIGN PARQUET

654 rue du Chalonge, P.A. du Haut-Montigné / 35370 Torcé / FRANCE

Tél. +33 (0)2 99 49 66 66 / Fax +33 (0)2 99 49 66 67

E-mail France : commercial@designparquet.fr

E-mail Export : export@designparquet.fr

www.designparquet.com

Previous data sheets are invalid. Errors or technical informations can be changes without notice.

Updated in : January 2026.